

# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)	O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)						
35	15	+2,0 -0	2,30	75	15	+3,0 -0	10,30						
	20		2,00		20		10,00						
	25		1,60		25		9,60						
40	15	+2,0 -0	3,00		80		27	+3,0 -0	9,40				
	20		2,70				30		9,10				
	25		2,30				35		8,60				
45	15	+2,0 -0	3,80				85		40	+3,0 -0	8,00		
	20		3,50						45		7,30		
	25		3,10						47,5		6,80		
	30		2,70						50		6,50		
50	15	+2,0 -0	4,60						90		55	+4,0 -0	5,60
	20		4,40								60		4,60
	25		4,00	15		11,70							
	30		3,50	20		11,30							
55	35	+3,0 -0	3,00	95		25					+4,0 -0		10,90
	40		5,65		27	10,70							
	42,5		5,30		30	10,50							
	45		4,90		35	10,00							
	50		4,50		40	9,30							
	55		3,90		45	8,60							
	60		3,30		50	7,80							
60	60	+3,0 -0	3,00		100	52,5	+4,0 -0	7,40					
	65		6,60			55		7,00					
	70		6,30			60		6,00					
	75		6,00			65		5,00					
	80		5,50			15		13,10					
	85		5,00	20		12,80							
	90		4,40	25		12,40							
65	42,5	+3,0 -0	4,10	105		27		+4,0 -0	12,20				
	45		3,60			30			11,90				
	50		7,80			32,5			11,65				
	55		7,50			35			11,40				
	60		7,10			40			10,80				
	65		6,90		42,5	10,40							
	70		6,60		45	10,10							
	75		6,10		47,5	9,70							
	80		5,10		50	9,30							
	85		4,80		52,5	8,90							
70	50	+3,0 -0	4,00		110	55	+4,0 -0		8,40				
	52,5		3,60			57,5			8,00				
	60		9,00	60		7,50							
	65		8,50	65		6,40							
	70		8,30	70		5,30							
	75		8,10	15		14,60							
	80		7,80	20		14,30							
	85		7,30	25		13,90							
	90		6,70	27		13,70							
	95		6,00	30		13,50							
100	5,20	32,5	13,20										
105	4,30	35	12,90										

O.D. < 400 mm : Maximum length 300 mm

O.D. > 400 mm : Maximum length 100 mm

\*Referred to Outer Diameter. Tolerance on Inner Diameter: -6% +0  
Edition 10.01

Weights stated are for guide purposes only



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it

# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)	O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)
90	37,5	+4,0 -0	12,60	105	15	+5,0 -0	20,10
	40		12,30		20		20,20
	42,5		12,00		27		19,60
	45		11,60		30		19,30
	47,5		11,20		35		18,80
	50		10,80		40		18,10
	52,5		10,40		45		17,40
	55		10,00		50		16,60
	57,5		9,50		55		15,70
	60		9,00		57,5		15,20
	62,5		8,50		60		14,80
	65		8,00		65		13,70
	67,5		7,40		70		12,60
	70		6,80		75		11,30
	72,5		6,30		80		10,00
75	5,60	85	8,60				
95	15	+4,0 -0	16,30	110	90	+5,0 -0	7,10
	20		15,90		92,5		6,20
	25		15,50		20		22,50
	27		15,30		25		22,10
	30		15,10		30		21,60
	35		14,60		35		21,10
	40		13,90		40		20,50
	45		13,20		45		19,70
	50		12,40		50		18,90
	52,5		12,00		55		18,00
	55		11,60		57,5		17,60
	60		10,60		60		17,10
	65		9,60		65		16,00
	70		8,50		70		14,90
	75		7,30		75		13,60
80	6,00	80	12,30				
100	15	+4,0 -0	18,30	115	85	+5,0 -0	10,90
	20		17,60		90		9,50
	25		17,20		95		7,90
	27		17,00		20		24,90
	30		16,80		25		24,50
	35		16,30		27		24,30
	40		15,60		30		24,10
	45		14,90		40		22,90
	47,5		14,60		45		22,20
	50		14,10		47,5		21,80
	55		13,30		50		21,40
	57,5		12,80		55		20,50
	60		12,30		60		19,50
	65		11,30		65		18,40
	70		10,20		67,5		17,90
75	9,00	70	17,30				
80	7,70	72,5	16,70				
85	6,30	75	16,10				

O.D. < 400 mm : Maximum length 300 mm

O.D. > 400 mm : Maximum length 100 mm

\*Referred to Outer Diameter. Tolerance on Inner Diameter: -6% +0  
Edition 10.01

Weights stated are for guide purposes only

SINCERT



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it

# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)	O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)		
115	80	+5,0 -0	14,80	130	65	+5,0 -0	25,10		
	85		13,40		70		23,90		
	90		11,90		75		22,70		
	95		10,30		80		21,40		
	100		8,30		85		20,00		
120	20	+5,0 -0	27,00		135		90	+5,0 -0	18,50
	30		26,20				95		16,90
	40		25,00				100		15,30
	45		24,30				105		13,60
	50		23,50				110		11,70
	55		22,60	115		9,80			
	60		21,60	25		33,50			
	65		20,60	30		33,10			
	70		19,40	40		31,90			
	75		18,20	50		30,40			
	80		16,90	55	29,50				
	85		15,50	60	28,50				
	90		14,00	65	27,40				
	92,5		13,20	70	26,30				
	95		12,40	75	25,10				
	100		10,80	80	23,80				
	105		9,10	85	22,40				
	125		25	+5,0 -0	29,30	140	90	+5,0 -0	20,90
27		29,10	95		19,30				
30		28,90	100		17,70				
40		27,70	105		15,90				
42,5		27,30	110		14,10				
45		26,90	115		12,20				
50		26,10	120		10,20				
52,5		25,70	20		36,50				
55		25,30	35		35,10				
60		24,30	40		34,40				
65		23,20	45		33,70				
70		22,10	50		32,90				
75		20,90	55		32,10				
77,5		20,20	60		31,10				
80		19,50	65		30,10				
85		18,20	70		28,90				
90		16,70	75		27,70				
95		15,10	80		26,40				
100		13,50	85		25,00				
105		11,70	90		23,60				
110	9,90	95	22,00						
130	20	+5,0 -0	31,50		100		20,40		
	25		31,20	105	18,70				
	40		29,50	110	16,90				
	45		28,80	115	15,00				
	50		28,00	120	13,00				
	55		27,10	125	11,00				
	60		26,10						

O.D. < 400 mm : Maximum length 300 mm

O.D. > 400 mm : Maximum length 100 mm

\*Referred to Outer Diameter. Tolerance on Inner Diameter: -6% +0  
Edition 10.01

Weights stated are for guide purposes only



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it

# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)	O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)				
145	40	+5,0 -0	37,00	155	90	+6,0 -0	31,50				
	45		36,30		95		29,90				
	50		35,50		100		28,40				
	60		33,60		105		26,60				
	65		32,60		110		24,70				
	70		31,50		115		22,90				
	75		30,30		120		20,90				
	80		29,00		125		18,90				
	85		27,60		130		16,80				
	90		26,10		135		14,70				
	95		24,60		140		11,90				
	100		22,90		145		9,10				
	105		21,20		25		47,30				
	110		19,40		40		45,70				
	115		17,50		47,5		44,50				
	120		15,60		50		44,10				
	125		13,50		55		43,20				
	130		11,40		65		41,20				
	150		20		+5,0 -0		41,60	160	70	+6,0 -0	40,10
			25				41,20		75		38,90
40		39,60	80	37,60							
45		38,90	85	36,20							
50		38,10	90	34,80							
55		37,20	95	33,30							
60		36,30	100	31,60							
65		35,20	105	29,90							
70		34,10	110	28,20							
75		32,90	115	26,30							
80		31,60	120	24,30							
85		30,20	125	22,30							
90		28,70	130	20,20							
95		27,20	135	18,00							
100		25,60	140	15,40							
105		23,80	145	12,50							
110		22,00	150	10,00							
115		20,20	35	49,20							
120		18,20	40	48,60							
125		16,10	47,5	47,40							
130	14,00	50	46,90								
135	11,80	60	45,10								
155	25	+6,0 -0	43,80	165	70	+6,0 -0	43,00				
	40		42,20		75		41,80				
	50		40,70		80		40,50				
	60		39,00		85		39,10				
	65		38,00		90		37,70				
	70		36,80		100		34,50				
	75		35,60		105		32,80				
	80		34,10		110		30,90				
85	33,00	115	29,20								

O.D. < 400 mm : Maximum length 300 mm

O.D. > 400 mm : Maximum length 100 mm

\*Referred to Outer Diameter. Tolerance on Inner Diameter: -6% +0  
Edition 10.01

Weights stated are for guide purposes only



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it

# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)	O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)		
165	120	+6,0 -0	27,20	180	50	+6,0 -0	56,80		
	125		25,20		60		55,00		
	130		23,10		70		52,80		
	135		20,90		80		50,30		
	140		18,10		85		48,90		
	145		15,30		90		47,50		
	150		12,80		95		45,90		
170	40	+6,0 -0	51,50		100		44,30		
	47,5		50,30		105		42,60		
	50		49,90		110		40,80		
	60		48,10		115		38,90		
	70		45,90		120		36,90		
	80		43,40		125		34,90		
	90		40,60		130		32,70		
	95		39,10		135		30,50		
	100		37,50		138		29,20		
	105		35,80		140		27,30		
	110		34,00		145		24,90		
	115		32,10		150		22,40		
	120		30,10		155		19,80		
	125		28,10		160		17,10		
	130		26,00	165	13,80				
	175		135	+6,0 -0	23,80	185	60	+8,0 -0	58,20
			140		21,10		65		57,20
145		18,20	70		56,00				
150		15,80	75		54,80				
155		13,20	80		53,50				
55		52,30	85		52,20				
60		51,50	90		50,70				
65		50,50	100		47,50				
70		49,30	105		45,80				
85		45,50	110		44,00				
90	44,00	115	42,10						
95	42,40	120	40,20						
100	40,80	125	38,10						
105	39,10	130	36,00						
110	37,30	135	33,80						
115	35,40	140	30,50						
120	33,50	145	28,10						
125	31,40	150	25,60						
130	29,30	155	23,00						
135	27,10	160	20,40						
140	23,80	165	17,00						
145	21,40	170	14,20						
150	18,90	190	40	+8,0 -0	64,90				
155	16,30		50		63,40				
160	13,70		60		61,50				
27	60,20		80		56,90				
180	30	+6,0 -0	59,40	85	55,50				
	40		58,30	90	54,00				

O.D. < 400 mm : Maximum length 300 mm

O.D. > 400 mm : Maximum length 100 mm

\*Referred to Outer Diameter. Tolerance on Inner Diameter: -6% +0  
Edition 10.01

Weights stated are for guide purposes only



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it

# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)	O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)
190	100	+8,0 -0	50,80	200	140	+8,0 -0	41,90
	105		49,10		145		39,00
	110		47,30		150		36,50
	115		45,40		155		34,00
	120		43,50		160		31,60
	125		41,40		165		28,30
	130		39,30		170		25,40
	135		37,10		175		22,40
	140		33,80		180		19,40
	145		31,40		185		15,90
	150		28,90		50		74,30
	155		26,30		70		70,30
	160		23,70		80		67,80
	165		20,40		85		66,40
	170		17,50		100		61,80
	175		14,60		105		60,10
	195		65		+8,0 -0		63,70
80		60,10	115	56,50			
100		54,10	120	54,50			
105		52,40	125	52,50			
115		48,80	130	50,40			
125		44,80	135	48,20			
130		42,70	140	45,50			
135		40,40	145	42,60			
140		37,70	150	40,10			
145		34,90	155	37,50			
150		32,40	160	34,90			
155		29,80	165	31,60			
160		27,10	170	28,80			
165		23,90	175	25,80			
170		21,20	180	22,90			
175		18,20	185	19,60			
180		15,10	50	77,90			
200	45	+8,0 -0	71,50	210	70	+8,0 -0	73,90
	47,5		71,10		80		71,40
	50		70,70		90		68,60
	60		68,90		95		67,10
	70		66,70		100		65,50
	75		65,50		115		60,10
	80		64,20		125		56,10
	90		61,40		130		54,00
	95		59,90		135		51,80
	100		58,30		140		49,10
	105		56,60		145		46,20
	110		54,80		150		43,70
	115		52,90		155		41,20
	120		51,00		160		38,50
	125		48,90		165		35,20
	130		46,80		170		32,40
	135		44,60		175		29,50

O.D. < 400 mm : Maximum length 300 mm

O.D. > 400 mm : Maximum length 100 mm

\*Referred to Outer Diameter. Tolerance on Inner Diameter: -6% +0  
Edition 10.01

Weights stated are for guide purposes only

SINCERT



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it

# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)	O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)		
210	180	+8,0 -0	26,50	225	140	+8,0 -0	60,70		
	185		23,10		145		57,80		
	195		17,70		150		55,30		
215	50	+8,0 -0	81,80		225		155	+8,0 -0	52,80
	80		74,30				160		50,10
	90		72,50				165		46,80
	95		71,00				170		44,00
	100		69,40				175		41,10
	115		64,00				180		38,10
	125		60,00				190		32,50
	130		57,90				195		29,30
	145		50,10				200		27,30
	150		47,60				205		24,00
	155		45,10				210		20,50
	160		42,40				45		94,70
	165		39,20	75		88,80			
	170		36,30	85		86,00			
	175		33,40	90		84,60			
	180		30,40	100	81,40				
	185		27,00	110	78,00				
	190		24,80	120	74,20				
	195		21,60	125	72,10				
	200		19,60	135	67,80				
220	50	+8,0 -0	85,60	230	140	+8,0 -0	64,60		
	70		81,60		145		62,20		
	80		79,20		150		59,70		
	90		76,30		155		57,30		
	100		73,20		160		54,50		
	110		69,80		168		51,20		
	115		67,80		170		48,40		
	125		63,90		175		45,50		
	130		61,70		180		42,50		
	135		59,50		185		39,10		
	140		56,80		195		34,50		
	145		53,90		200		31,80		
	150		51,40		205		28,40		
	155		48,90		210		24,90		
	160		46,20		215		20,20		
	165		43,00	110	81,60				
	170		40,10	115	79,60				
	175		37,20	120	77,80				
	180		34,20	140	68,20				
	185		30,50	170	52,00				
	190		28,60	180	46,60				
	195		25,40	185	43,10				
	200		23,40	195	38,20				
	205		20,10	200	35,50				
	225		110	+8,0 -0	73,60	235	205	+8,0 -0	32,10
120		69,80	210		28,90				
125		67,70	215		23,50				
135		63,40	220		19,80				

O.D. < 400 mm : Maximum length 300 mm

O.D. > 400 mm : Maximum length 100 mm

\*Referred to Outer Diameter. Tolerance on Inner Diameter: -6% +0  
Edition 10.01

Weights stated are for guide purposes only

SINCERT



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it

# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)	O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)				
240	80	+8,0 -0	97,00	250	215	+8,0 -0	38,20				
	100		90,90		220		34,50				
	120		83,50		225		30,00				
	135		77,00		230		26,10				
	150		68,80		235		22,10				
	155		66,20		255		75	+8,0 -0	113,80		
	160		63,50	95		108,10					
	170		57,20	150		84,20					
	180		51,20	170		72,70					
	185		47,70	175		69,70					
	195		42,90	180		66,70					
	200		40,20	185		63,20					
	205		36,80	205		52,20					
	210		33,30	210		48,70					
	215		28,60	215		43,70					
	220		24,50	220		40,00					
	225		19,90	225		35,40					
	245		110	+8,0 -0	92,10	260	230	+8,0 -0	31,50		
150		73,50	235		27,50						
165		64,90	240		23,40						
170		62,00	50		123,70						
175		59,00	55		121,20						
180		56,00	75		118,40						
200		44,90	90		114,20						
210		38,00	95		112,70						
215		32,90	100		111,00						
220		29,20	110		107,50						
225		24,70	125		101,50						
230		20,80	135		97,10						
250		40	+8,0 -0		115,20		260		140	+8,0 -0	93,80
		70			109,60				145		91,40
	80	107,10		150	88,80						
	90	104,20		155	86,20						
	100	101,00		160	83,50						
	110	97,40		165	80,20						
	120	93,50		175	74,30						
	130	89,30		180	71,30						
	140	83,80		185	67,80						
	150	78,80		195	62,90						
	155	76,20		200	60,30						
	160	73,50		205	56,80						
	170	67,30		210	53,30						
	175	64,30		215	48,30						
	180	61,20		220	44,60						
	185	57,80		225	40,00						
	195	52,90		230	36,10						
	200	50,20		235	32,10						
205	46,80	240	28,00								
210	43,30	245	23,00								

O.D. < 400 mm : Maximum length 300 mm

O.D. > 400 mm : Maximum length 100 mm

\*Referred to Outer Diameter. Tolerance on Inner Diameter: -6% +0  
Edition 10.01

Weights stated are for guide purposes only

SINCERT



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it



# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)	O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)
265	140	+8,0 -0	98,50	280	150	+8,0 -0	108,10
	170		81,70		160		102,80
	180		76,00		165		99,50
	205		61,50		180		90,60
	215		53,70		195		82,20
	220		49,30		200		79,60
	225		44,70		210		72,60
	240		32,70		215		67,60
	250		21,80		220		63,80
270	70	+8,0 -0	129,10	285	230	+8,0 -0	55,40
	90		123,70		240		47,30
	130		108,80		245		42,30
	145		100,80		250		36,40
	150		98,30		255		32,90
	155		95,70		265		23,90
	170		86,80		90		137,70
	175		83,80		145		116,20
	180		80,80		160		109,70
	185		77,30		180		97,40
	195		72,40		185		94,00
	200		69,70		210		79,50
	205		66,30		215		74,40
	210		62,80		220		70,70
	215		57,70		230		62,20
	220		54,00		235		58,30
	225		49,50		240		54,20
	230		45,60		245		49,20
	235		41,60		250		43,20
	240		37,50		265		30,80
	245		32,50		95		144,70
	250		26,50		170		109,30
	255		23,00		200		92,30
	275		200		+8,0 -0		200
210		170	80,70				
215		150	76,60				
220		130	72,00				
230		110	68,10				
235		90	60,10				
245		70	55,10				
250		50	49,10				
255		30	45,60				
260		10	36,60				
270		0	33,40				
275		0	27,80				
280		0	103,50				
285		0	96,00				
280	60	+8,0 -0	141,10	295	185	+8,0 -0	49,30
	100		130,30		200		37,10
	135		116,40		255		26,20

O.D. < 400 mm : Maximum length 300 mm

O.D. > 400 mm : Maximum length 100 mm

\*Referred to Outer Diameter. Tolerance on Inner Diameter: -6% +0  
Edition 10.01

Weights stated are for guide purposes only



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it

# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)	O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)
300	80	+8,0 -0	157,00	310	275	+8,0 -0	51,50
	100		150,90		285		41,40
	120		143,50		70		183,80
	145		131,30		140		158,00
	150		128,80		150		153,00
	170		117,20		175		138,50
	180		111,20	195	127,10		
	195		102,90	205	121,00		
	200		100,20	215	112,50		
	205		96,80	225	104,20		
	210		93,30	230	100,30		
	215		88,20	240	92,20		
	220		84,50	245	87,20		
	230		76,00	250	81,30		
	235		72,00	255	77,80		
	240		68,00	270	65,60		
	245		63,00	275	60,00		
	250		57,00	280	54,70		
	255		53,50	285	49,90		
	265		44,50	298	38,90		
	270		41,30	305	28,50		
	275		35,70	255	83,50		
	285		25,60	270	71,30		
	305		185	+8,0 -0	178,70		325
210		104,10	305		34,20		
215		99,00	120		182,90		
220		95,30	160		162,80		
235		82,90	165		159,50		
245		73,80	185		146,80		
250		67,80	200		139,60		
255		64,30	210		132,60		
265		55,40	215		127,60		
275		46,50	245		102,30		
285		36,40	250		96,40		
290		31,50	255		92,90		
310	70	+8,0 -0	175,40	330	265	+8,0 -0	83,90
	100		166,70		270		80,70
	150		144,60		275		75,10
	165		135,90		285		65,00
	195		118,70		298		54,00
	200		116,00		300		48,80
	215		104,00	305	43,60		
	225		95,70	310	39,40		
	235		87,80	315	34,00		
	240		83,80	195	148,20		
	245		78,80	210	138,60		
	250		72,80	220	129,80		
	255		69,30	240	113,30		
	265		60,30	255	98,80		
	270		57,10	265	89,90		

O.D. < 400 mm : Maximum length 300 mm

O.D. > 400 mm : Maximum length 100 mm

\*Referred to Outer Diameter. Tolerance on Inner Diameter: -6% +0  
Edition 10.01

Weights stated are for guide purposes only



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it

# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)	O.D. (mm)	I.D. (mm)	Tolerance* (mm)	Weight (g/mm)				
340	270	+8,0 -0	86,70	370	175	to be agreed	197,10				
	285		70,90		200		183,10				
	298		59,90		250		139,90				
	305		49,60		270		124,70				
	315		40,00		285		108,50				
	320		34,50		298		97,50				
	325		26,70		305		87,10				
345	60	+8,0 -0	213,70	380	315	to be agreed	77,50				
	240		119,30		325		64,30				
	245		114,40		335		55,20				
	255		104,90		345		41,10				
	270		92,70		205		202,30				
	285		77,00		230		181,50				
	290		72,00		235		177,60				
	298		67,00		250		162,50				
	305		55,60		255		159,00				
	315		46,00		265		150,10				
	320		40,60				140,80				
	325						131,10				
	330						126,20				
	350		200		to be agreed			390		to be agreed	120,10
215				109,80							
230				100,20							
245				94,70							
250				86,90							
255				77,80							
265				63,80							
275				49,20							
285				256,80							
290				211,70							
298				180,50							
305				149,10							
315				138,10							
320				127,70							
360		225	to be agreed			405	305		to be agreed		112,70
		280					335				95,80
	285			350	81,70						
	290			355	73,10						
	300			360	67,20						
	305			370	53,50						
	315			135	276,60						
	325			145	296,60						
	340			240	207,50						
	345			298	154,20						
	370	50		to be agreed	246,50			315		to be agreed	134,20
150		211,70			320	128,70					
					335	121,00					
					360		83,30				
					370		69,50				

O.D. < 400 mm : Maximum length 300 mm

O.D. > 400 mm : Maximum length 100 mm

\*Referred to Outer Diameter. Tolerance on Inner Diameter: -6% +0  
Edition 10.01

Weights stated are for guide purposes only



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it

# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance (mm)	Weight (g/mm)	O.D. (mm)	I.D. (mm)	Tolerance (mm)	Weight (g/mm)				
410	90	to be agreed	299,10	465	170	to be agreed	347,30				
	200		245,10		290		250,70				
	265		189,50		315		224,70				
	295		164,60		335		202,40				
	320		134,10		345		188,30				
	325		126,30		360		173,80				
	330		120,10		385		140,60				
	345		103,20		390		134,00				
	360		88,60		400		113,60				
	370		74,90		410		99,50				
	385		55,50		425		77,80				
	390		48,80		445		47,70				
	395		35,30		230		331,10				
	425		230		to be agreed		243,20	480	335	to be agreed	227,40
275		202,40	345	213,30							
285		192,70	360	198,80							
310		171,40	385	165,60							
315		161,80	390	159,00							
325		148,50	400	138,50							
335		139,40	410	124,50							
345		125,40	425	101,30							
360		110,90	445	72,70							
370		97,10	460	49,20							
385		77,70	320	261,30							
398		57,50	360	215,90							
400		50,60	385	182,70							
440		90	to be agreed	344,30		490	400		to be agreed		155,60
	200	290,30		410	141,60						
	255	243,60		425	118,40						
	320	179,30		445	89,80						
	340	156,60		460	66,30						
	345	148,40		305	303,70						
	360	133,80		345	256,70						
	370	120,10		385	209,00						
	385	100,70		400	181,90						
	390	94,00		410	167,90						
	398	80,50		425	144,70						
	400	73,60		445	116,00						
	410	59,50		460	92,60						
	450	100		to be agreed	356,00		500	475		to be agreed	68,30
215		300,40	110		472,80						
315		206,80	285		351,00						
335		184,50	335		297,70						
340		175,20	400		208,90						
360		155,90	410		194,90						
370		142,20	425		171,70						
385		122,80	445		143,10						
400		95,70	460		119,60						
410		81,70	475		95,40						
425		58,50	485		77,10						
450		100	to be agreed		356,00	515		110	to be agreed		472,80
		215			300,40			285			351,00
		315			206,80			335			297,70
	335	184,50		400	208,90						
	340	175,20		410	194,90						
	360	155,90		425	171,70						
	370	142,20		445	143,10						
	385	122,80		460	119,60						
	400	95,70		475	95,40						
	410	81,70		485	77,10						
	425	58,50									

O.D. < 400 mm : Maximum length 300 mm

O.D. > 400 mm : Maximum length 100 mm

Edition 10.01

Weights stated are for guide purposes only



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it

# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance (mm)	Weight (g/mm)	O.D. (mm)	I.D. (mm)	Tolerance (mm)	Weight (g/mm)
530	385	to be agreed	263,80	590	540	to be agreed	138,50
	425		199,50		560		100,70
	445		170,90		390		429,00
	460		147,40		415		394,50
	475		123,20		430		371,30
	485		104,90		445		342,70
	505		74,10		460		319,20
545	145	to be agreed	510,00	610	470	to be agreed	303,10
	360		325,50		475		295,00
	388		292,30		485		276,70
	400		265,30		505		246,00
	410		251,20		515		226,60
	425		228,00		530		199,60
	445		199,40		540		181,20
	460		175,90		560		143,30
	475		151,70		580		104,00
	485		113,40		590		83,90
	495		116,50		475		334,40
	505		102,70		490		303,50
	515		83,40		505		284,40
560	290	to be agreed	428,70	620	515	to be agreed	264,70
	320		398,30		540		218,30
	400		292,60		560		179,70
	425		255,40		580		139,60
	445		226,70		590		119,10
	460		203,30		345		549,80
	475		179,00		390		495,40
	495		160,80		460		385,70
	505		130,00		505		312,50
	515		110,70		515		293,10
	530		83,70		530		266,10
570	540	to be agreed	65,20	640	540	to be agreed	247,70
	220		523,40		560		209,80
	250		499,00		580		170,50
	360		384,90		590		150,40
	445		258,80		600		129,90
	485		192,80		615		96,50
	495		175,90		475		407,50
	505		162,10		495		372,30
	515		142,70		580		216,50
	530		115,70		590		194,40
590	540	to be agreed	97,30	655	600	to be agreed	175,90
	390		386,30		615		142,50
	400		365,90		630		112,50
	410		351,90		445		490,60
	475		252,40		540		329,10
	485		234,10		580		251,90
	505		203,30		600		211,30
	515		184,00		630		147,90
	530		157,00		650		103,90

O.D. < 400 mm : Maximum length 300 mm

O.D. > 400 mm : Maximum length 100 mm

Edition 10.01

Weights stated are for guide purposes only



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it

# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance (mm)	Weight (g/mm)	O.D. (mm)	I.D. (mm)	Tolerance (mm)	Weight (g/mm)
680	360	to be agreed	648,00	790	760	to be agreed	176,50
	600		242,60		770		137,00
	615		209,20	815	600	to be agreed	621,70
	630		179,20		700		398,40
	650		135,20		760		248,20
690	540	to be agreed	389,80	840	770	to be agreed	208,70
	580		312,60		785		168,50
	600		272,00	860	720	to be agreed	420,50
	615		238,60		735		383,00
	630		208,60		785		293,30
	650		164,60		800		198,30
	670		119,30		815		156,60
700	450	to be agreed	540,50	880	490	to be agreed	954,10
	580		350,00		745		400,80
	600		309,40	900	760	to be agreed	367,30
	615		276,00		785		287,60
	630		246,00		785		349,20
	650		202,00		800		308,20
	670		156,70		815		266,40
720	515	to be agreed	510,80	910	835	to be agreed	209,60
	580		388,20		860		136,60
	615		314,20	930	760	to be agreed	504,50
	670		194,90		785		424,80
	680		160,00		800		383,90
	700		124,30		815		342,10
740	600	to be agreed	386,60	950	845	to be agreed	285,30
	630		323,10		860		212,30
	680		198,90	965	600	to be agreed	929,60
	700		163,30		730		620,10
	715		114,60		815		393,60
	720		94,70		860		263,90
750	490	to be agreed	639,60	990	885	to be agreed	188,80
	580		458,00		860		329,50
	615		392,80	1000	885	to be agreed	254,40
	670		273,50		815		526,30
	700		203,00		860		396,50
	715		154,30		925		196,90
	730		116,90		885		389,80
770	580	to be agreed	521,00	1050	925	to be agreed	265,30
	615		447,00		945		201,00
	650		373,00	1000	650	to be agreed	1124,60
	700		257,10		860		566,30
	715		208,40		920		398,40
	730		171,00		945		302,50
	745		140,50		970		223,50
790	650	to be agreed	442,60	1050	925	to be agreed	570,80
	670		397,20		970		427,60
	700		326,70		990		356,90
	715		278,00		1000		305,60
	735		240,60		1020		231,20

O.D. < 400 mm : Maximum length 300 mm

O.D. > 400 mm : Maximum length 100 mm

Edition 10.01

Weights stated are for guide purposes only



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it

# Molded Tubes - Virgin p.t.f.e.

## Nominal Sizes

O.D. (mm)	I.D. (mm)	Tolerance (mm)	Weight (g/mm)
1120	925	to be agreed	900,30
	945		804,40
	1000		603,50
	1040		462,70
	1080		335,10
1200	1040	to be agreed	793,50
	1130		453,10
	1160		338,70
1215	1130	to be agreed	534,80
	1160		420,50
1260	1080	to be agreed	932,60
	1160		605,50
	1200		422,40
	1220		313,50
1300	1200	to be agreed	567,40
	1220		458,50
	1280		225,00
1320	1300	to be agreed	275,10
1340	1130	to be agreed	1112,50
	1280		472,70
	1300		383,70
1380	1220	to be agreed	948,60
	1300		626,10
	1340		453,40
1440	1300	to be agreed	933,30
	1380		563,90
	1400		444,00
	1420		331,80

O.D. < 400 mm : Maximum length 300 mm

Edition 10.01

O.D. > 400 mm : Maximum length 100 mm

**Weights stated are for guide purposes only**



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it