

# Molded Rods - Virgin p.t.f.e.

## Nominal Sizes

ø (mm)	Tolerance (mm)	Weight (g/mm)	Max length (mm)		ø (mm)	Tolerance (mm)	Weight (g/mm)	Max length (mm)	
			300	1000				80	300
30	+1,2 -0	1,8	● *		245	+6,0 -0	111,2		●
35	+1,6 -0	2,5	● *		250	+6,0 -0	116,0		●
40	+1,6 -0	3,3	● *		255	+6,0 -0	122,3		●
45	+2,0 -0	4,0	●		260	+6,0 -0	126,7		●
50	+2,0 -0	4,8	●		265	+6,0 -0	131,0		●
55	+2,4 -0	6,0	●		270	+6,0 -0	135,7		●
60	+2,4 -0	7,2	●		280	+6,0 -0	146,0		●
65	+2,8 -0	8,3	●		285	+6,0 -0	152,2		●
70	+2,8 -0	9,5	●		290	+6,0 -0	158,0		●
75	+3,2 -0	10,8	●		300	+6,0 -0	166,3		●
80	+3,2 -0	12,3	●		310	+6,0 -0	179,3		●
85	+3,6 -0	14,0	●		315	+6,0 -0	181,4		●
90	+3,6 -0	15,2	●		320	+8,0 -0	189,7		●
95	+4,0 -0	16,9	●		330	+8,0 -0	212,0		●
100	+4,0 -0	19,2	●		335	+8,0 -0	213,0		●
105	+5,0 -0	20,7	●		340	+8,0 -0	216,6		●
110	+5,0 -0	23,0	●		345	+8,0 -0	221,3		●
115	+5,0 -0	26,0	●		350	+8,0 -0	236,0		●
120	+5,0 -0	27,7	●		365	+8,0 -0	250,6		●
125	+5,0 -0	29,7	●		380	+10,0 -0	273,2		●
130	+5,0 -0	31,5	●		395	+10,0 -0	291,1		●
135	+5,0 -0	34,3	●		400	+10,0 -0	307,2		●
140	+5,0 -0	37,3	●		410	+10,0 -0	312,6	●	
145	+5,0 -0	39,6	●		420	+12,0 -0	339,0	●	
150	+5,0 -0	42,3	●		435	+12,0 -0	357,7	●	
155	+6,0 -0	45,3	●		450	+12,0 -0	390,0	●	
160	+6,0 -0	48,7	●		460	+12,0 -0	397,6	●	
165	+6,0 -0	51,5	●		470	+12,0 -0	416,8	●	
170	+6,0 -0	55,0	●		480	+12,0 -0	434,7	●	
175	+6,0 -0	57,5	●		500	+12,0 -0	465,9	●	
180	+6,0 -0	60,7	●	●	525	+12,0 -0	520,7	●	
185	+6,0 -0	64,1	●		540	+12,0 -0	549,2	●	
190	+6,0 -0	69,6	●		560	+12,0 -0	576,5	●	
195	+6,0 -0	70,9	●		585	+12,0 -0	645,7	●	
200	+6,0 -0	73,0	●	●	600	+12,0 -0	679,2	●	
205	+6,0 -0	79,0	●		620	+12,0 -0	725,3	●	
210	+6,0 -0	82,7	●		635	+12,0 -0	760,8	●	
215	+6,0 -0	88,7	●		650	+12,0 -0	797,1	●	
220	+6,0 -0	90,3	●		690	+12,0 -0	898,3	●	
225	+6,0 -0	95,0	●		700	+15,0 -0	924,5	●	
230	+6,0 -0	97,5	●		720	+15,0 -0	976,5	●	
235	+6,0 -0	102,0	●		750	+15,0 -0	1061,3	●	
240	+6,0 -0	107,0	●		770	+15,0 -0	1118,7	●	

● Additional production  
● Standard production

Tolerance on length: +15mm -0  
\* Max length 200 mm

Weights stated are for guide purposes only

Edition 10.01



**fluorseals**<sup>spa</sup>  
prodotti in p.t.f.e.

Company Quality System cert. IIP N°061 first issue 1994/07/01 - Current issue 2009/06 UNI EN ISO 9001:2008

24064 Grumello del Monte Bg Italy - Via Tribolina, 20/22 - Tel. +39 035 4492811 - Fax +39 035 831410 - www.fluorseals.it - info@fluorseals.it